

## RH-20A Specification



Power of solar panel DC17V/20W 1pc 3.0KG/pc 650X306X17mm Energy Board line 5m 1pc 0.3KG

Controller Box: 1pc 13KG 240X210X220mm

## **Application Hours**

solar p	anel
---------	------

Vm(V) 17.2V Voc(V) 21.4V Im(A) 1.162A Isc(A) 1.243A

5 hours sunshine generate 5.8Ah. One 12v/2w LED lamp can **light** 34.8 hours.

### **Controller Box**

DC 12V outlet Use for 12V DC lamp

DC 5V outlet Digital Product Charge

DC 6V outlet Digital Product Fast Charge

AC 220~240V 50Hz

American socket
GS outlet

Controller 12V5A

Lead-Acid Battery 12V24Ah

Battery charged full. One 12v/2w LED lamp can light 100 hours.

### Inverter

Input voltage: DC 12V Output voltage: 220~240V Over load protection: >300W Output Max Power: 300W

Output Rated Power: 150W

### Package Dimension



Each Component packed individually Controller Box: 320×230×255mm Solar panels : 660X316X27mm

Net Weight : 16.5KG, Gross Weight: 17.5KG

### Unit Price:

MOQ

## **Terms and Conditions**

Payment Terms : Shipment : Min. Order Quantity : Delivery date :



### RH-40A

### Specification

Power of solar panel
Energy Board line
Controller Box:

17.6V/40W 1pc 5m 2pc


2pc 1KG

1pc 13KG 240X210X220mm

5.5KG/pc

630X541X30mm





## solar panel

Vm(V) 17.6V Voc(V) 21.8V Im(A) 2.27A Isc(A) 2.48A

5 hours sunshine generate 11.35Ah. One 12v/2w LED lamp can light 68 hours.



#### **Controller Box**

DC 12V outlet Use for 12V DC lamp
DC 5V outlet Digital Product Charge
DC 6V outlet Digital Product Fast Charge

AC 220~240V 50Hz

American socket
GS outlet

Controller 12V5A

Lead-Acid Battery 12V24Ah

Battery charged full. One 12v/2w LED lamp can light 100 hours.

Inverter



Input voltage: DC 12V Output voltage: 220~240V Over load protection: >300W Output Max Power: 300W

Output Rated Power: 150W



Each Component packed individually Controller Box: 320×230×255mm Solar panels: 640X551X40mm

Net Weight: 19.5KG, Gross Weight: 20.5KG



### Unit Price:

MOQ

### **Terms and Conditions**

Payment Terms : Shipment : Min. Order Quantity : Delivery date :



# RH-80A

## **Specification**

Power of solar panel 17.2V/80W 1pc 8KG/pc 1195X541X30mm

Energy Board line 5m 2pc 1KG

Controller Box: 30KG 450X220X300mm 1pc



### **Application Hours**

	solar panel		
Vm(V)	17.2V	Voc(V)	21.6V

Im(A) 4.65A Isc(A) 5A 5 hours sunshine generate 23.25Ah. One 12v/2w LED lamp can light 139.5 hours.

_	<u> </u>
Controller Box	
DC 12V outlet	Use for 12V DC lamp
DC 5V outlet Digital Product Charge	
DC 6V outlet	Digital Product Fast Charge
AC 220~240V 50Hz	American socket
AO 220~240 V 30112	GS outlet
Controller	12V5A
	_

Со Lead-Acid Battery 12V70Ah

Battery charged full. One 12v/2w LED lamp can light 294 hours.

### Inverter

Input voltage: DC 12V Output voltage: 220~240V Over load protection: >500W Output Max Power: 500W

Output Rated Power: 250W

## Package Dimension

Each Component packed individually Controller Box: 555×315×515mm Solar panels : 1205X551X40mm

Net Weight : 39KG, Gross Weight: 40.5KG





#### Unit Price:

MOQ

# Terms and Conditions

Payment Terms Shipment

Min. Order Quantity: Delivery date



### **RH-160A**

#### **Specification**

Power of solar panel Energy Board line

17.2V/80W 8KG/pc 1195X541X30mm 2pc 1KG 5m 4pc

450X220X300mm

2рс

Controller Box: 38.5KG 1pc



### **Application Hours**

sol	ar panel		
/m(V)	17.2V	Voc(V)	21.6V
m(A)	4.65A	Isc(A)	5A

hours sunshine generate 46.5Ah. One 12v/2w LED lamp can light 279 hours.

## **Controller Box**

DC 12V outlet	Use for 12V DC lamp
DC 5V outlet	Digital Product Charge
DC 6V outlet	Digital Product Fast Charge
AC 220~240\/ 50Hz	American socket

GS outlet 12V10A Controller

12V100Ah Battery charged full. One 12v/2w LED lamp can light 420 hours.



Input voltage: DC 12V Output voltage: 220~240V Over load protection: >500W Output Max Power: 500W

Output Rated Power: 250W



### Package Dimension

Lead-Acid Battery

Each Component packed individually Controller Box:: 555×315×515mm Solar panels : 1205X551X80mm

Net Weight : 47.5KG, Gross Weight: 49KG



### Unit Price:

MOQ

# **Terms and Conditions**

Payment Terms Shipment Min. Order Quantity: Delivery date



RS-10D Specification

Power of solar panel DC 17V/10W 1pc 1.80KG/pc 360X305X16mm

Controller 12V/5A 1pc 0.15KG Lead-Acid Battery 12V/7AH 1pc 2.2KG

LED Lamp 12V/2W 2pc 1.0KG With 5meters wire

**Application** 

Applications Hours for using

Battery charged 1 day by the sunshine

LED Lamp 2W 1pc 16hours
LED Lamps 2W 2pcs 8hours

Battery is charged full of electricity

LED Lamp 2W 1pc 30hours
LED Lamps 2W 2pcs 15hours

After discharged completely, battery can be charged full by 2days (illumination

time: 5hours)

Package Dimension

Solar panels: 370X315X25mm, Lamp: 160X160x180mm 2pc Controller: 100X30X140mm Battery: 170X80X120mm

Each Component packed individually, then packed in one big carton

Dimension of Big Carton: 380X330X170mm

Net Weight : 6.5KG, Gross Weight: 8.5KG

Unit Price: MOQ :

### **Terms and Conditions**

Payment Terms : Shipment : Min. Order Quantity :

Delivery date :



# RB-5A Specification

Portable power 1pc 2.6KG/pc 268×125×202mm

Power adapter 1pc 0.3KG

# Application Hours

### Power adapter

input voltage: AC 220V Output voltage: 14~16V

Maximum current :500MA

The charge for an hour, storage power 0.5Ah

### Portable power

Color	Sparkling+Silver grey
DC 12V outlet	Use for 12V DC lamp
USB outlet	Digital Product Charge
Charging outlet	Charge for Portable power
·	·

Lead-Acid Battery 12V4Ah

When the battery is full, the front light can be bright time of up to 267 hours;

the side light can be bright time of up to 120 hours.

Radio frequency range	87.5-108MHz
Front light	3LED each LED 1500-2000mcd
Side light	8LED each LED 1000-1500mcd
Solar panel	18V4W

### Package Dimension

1PC/ COLORBOX; 6PCS/CTN Color box: 310×160×245mm Out box: 490X320X500mm

Net Weight: 18KG, Gross Weight: 19KG

### Unit Price:

MOQ

# Terms and Conditions

Payment Terms
Shipment
Shin. Order Quantity
Delivery date





RB-5B Specification

Portable power 1pc 2.6KG/pc 268×125×202mm

Power adapter 1pc 0.3KG

Cable 1pc 0.2KG 1m

Application Hours

Power adapter

input voltage: AC 220V Output voltage: 14~16V

Maximum current :500MA

The charge for an hour, storage power 0.5Ah

Portable power

Color White porcelain+Grass Green

DC 12V outlet Use for 12V DC lamp
USB outlet Digital Product Charge
Charging outlet Charge for Portable power

Lead-Acid Battery 12V4Ah

When the battery is full, the light can be bright time of up to 120 hours.

Radio frequency range 87.5-108MHz

Light 8LED each LED 1000-1500mcd

Solar panel 18V4W

Package Dimension

1PC/ COLORBOX; 6PCS/CTN Color box : 200×140×380mm

Out box : 430X410X390mm

Net Weight: 18KG, Gross Weight: 19KG

**Unit Price:** 

MOQ

## **Terms and Conditions**

Payment Terms
Shipment

Min. Order Quantity

Delivery date

